



Fixprim

Consolidating undercoat

Description

Consolidating undercoat that unifies the surface by levelling the porosity of the substrate. Compatible with all water-based or alkyd-based finishing products. Ideal as a primer before applying wallpaper. Highly matt finish.

Substrates

Is to be applied on indoor slightly absorbent and/or slightly chalky walls and ceilings made of plaster(boards), concrete, cement basecoat or bricks.

Properties

• Binder:	acrylic copolymers and drying resin
• Solid fillers:	titanium dioxide and mineral fillers
• Solvents:	water and glycols
• Density:	± 1.28
• Solid content by weight:	± 58%
• Solid content by volume:	± 38%
• Gloss unit:	matt (2 GU at 60°)
• Recommended film thickness per layer	
Dry:	33 µm - 45 µm
Wet:	90 µm - 125 µm

VOC content

This product contains at most 30 g/l.
EU limit value for this product (Cat. A/g): 30 g/l (2010).

Drying time at 20 °C

• Touch dry:	30 minutes
• Recoatable:	5 hours
• Hard:	2 to 3 days

Coverage

8 to 11 m²/l depending on substrate type and manner of application.

Dilution ratio

5 to 10% water.

The effectiveness of our products and systems is based on in-depth laboratory research and many years of practical experience. However, we accept no liability for any problems that may arise, as the final result may be influenced by a number of factors of which we are not necessarily aware. 08/09/2026 version.



Fixprim

Consolidating undercoat

Airless spray gun (tested at 20 °C with a non-dyed product)

- **Pressure:** 100 - 120 bars
- **Nozzle:** 0.015" - 0.021"
- **Angle:** 40° - 60°
- **Dilution:** 0%
- **Maximum spreading rate per coat:** 4 m²/l

Characteristics

- Sets particles.
- Better adhesion than latex or acrylic paint.
- Isolates and hardens substrates.
- Prevents sinkage and evens out substrate porosity.

Packaging options

4 l - 10 l

Application conditions

Ambient temperature between 10°C and 25°C with a substrate humidity of maximum 10%.

Application instructions

- The product is to be applied on a sound, clean and dry substrate.
- Glossy substrates are to be sanded before starting with application.
- Chalky or very absorbent substrates are to be treated with a consolidating primer beforehand.
- Dirty or infected (fungi and moulds) substrates are to be cleaned and degreased as well as undergo appropriate treatment.

Storing & disposal

Store the product in its original unopened packaging in a cool place, protected from frost and direct sunlight. Dispose of empty containers at an appropriate waste collection facility. Dispose of product residues in accordance with applicable local and national regulations.

Safety

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Get medical attention if you feel unwell. If medical advice is needed, have product container or label at hand. Dispose of contents and container in accordance with local, regional, national or international regulations. Contains biocidal products (preservatives). Contains: 1,2-benzisothiazol-3(2H)-one + CMIT/MIT (3:1). May produce an allergic reaction.