



Viscomatt

Washable decorative paint

Description

Very washable high-viscosity finish paint made of vinyl copolymers. Matt finish.

Substrates

Is to be applied on indoor and outdoor walls made of plaster(boards), wallpaper, glass mat, concrete, cement basecoat, particle boards, etc.

Also appropriate for unpainted indoor substrates (only when non-absorbent and non-chalky).

Properties

• Binder:	vinyl copolymers
• Solid fillers:	titanium dioxide and mineral fillers
• Solvents:	water and glycols
• Density:	± 1.45
• Solid content by weight:	± 64%
• Solid content by volume:	± 45%
• Gloss unit:	matt (2 GU at 60°)
• Covering power:	class 1
• Wet abrasion resistance:	class 1 according to DIN EN 13300
• Recommended film thickness per layer	
Dry:	43 µm - 53 µm
Wet:	100 µm - 125 µm

VOC content

This product contains at most 30 g/l.

EU limit value for this product (Cat. A/a): 30 g/l (2010).

Drying time at 20 °C

• Touch dry:	30 minutes
• Recoatable:	4 hours
• Hard:	2 to 3 days

Coverage

8 to 10 m²/l depending on substrate type and manner of application.

Dilution ratio

5 to 10% water

The effectiveness of our products and systems is based on in-depth laboratory research and many years of practical experience. However, we accept no liability for any problems that may arise, as the final result may be influenced by a number of factors of which we are not necessarily aware. 08/09/2026 version.



Viscomatt

Washable decorative paint

Airless spray gun (tested at 20 °C with a non-dyed product)

- **Pressure:** 140 - 150 bars
- **Nozzle:** 0.015" - 0.019"
- **Angle:** 40° - 60°
- **Dilution:** 0%
- **Maximum spreading rate per coat:** 8 m²/l

Characteristics

- Easy application.
- Very good hiding power.
- High level of whiteness.
- Permeable to water vapour.
- No splashes.
- Nonsaponifiable.
- Very good durability outdoors.
- Easy upkeep: washable.

Packaging options

1l - 2.5l - 4l - 10l

Application conditions

Ambient temperature between 10°C and 25°C with a substrate humidity of maximum 10%.

Application instructions

- The product is to be applied on a sound, clean and dry substrate.
- Glossy substrates are to be sanded before starting with application.
- Chalky or very absorbent substrates are to be treated with a consolidating primer beforehand.
- Dirty or infected (fungi and moulds) substrates are to be cleaned and degreased as well as undergo appropriate treatment.

Storing & disposal

Store the product in its original unopened packaging in a cool place, protected from frost and direct sunlight. Dispose of empty containers at an appropriate waste collection facility. Dispose of product residues in accordance with applicable local and national regulations.

Safety

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Get medical attention if you feel unwell. If medical advice is needed, have product container or label at hand. Dispose of contents and container in accordance with local, regional, national or international regulations. Contains biocidal products (preservatives). Contains: 1,2-benzisothiazol-3(2H)-one + CMIT/MIT (3:1). May produce an allergic reaction.