@Attak

INDOOR AIR EMISSIONS A+ A+ A B C



Vinirock 15

Facade rendering - medium grit (1.5 mm)

Description

Decorative and protective roughcast made from a dispersion of non-saponifiable vinyl copolymer. Exhibits high resistance to weathering, UV rays and temperature changes.

Substrates

Is to be applied on facades and indoor or outdoor walls made of concrete, cement basecoat, bricks, plaster(boards), etc.

Properties

- **Binder:** vinyl copolymers
- **Solid fillers:** titanium dioxide and mineral fillers with studied granulometric distribution
- **Solvents:** water
- **Density:** ± 1.67
- **Solid content by weight:** ± 74%
- **Solid content by volume:** ± 57%
- **Gloss unit:** matt

VOC content

This product contains at most 40 g/l.
EU limit value for this product (Cat. A/c): 40 g/l (2010).

Drying time at 20 °C

- **Touch dry:** 5 hours
- **Recoatable:** 24 hours
- **Hard:** 2 to 3 days

Coverage

2 to 4 kg/m² depending on substrate type and manner of application.

Dilution ratio

Up to 10% water.

The effectiveness of our products and systems is based on in-depth laboratory research and many years of practical experience. However, we accept no liability for any problems that may arise, as the final result may be influenced by a number of factors of which we are not necessarily aware. 24/09/2026 version.

@Attak



Vinirock 15

Facade rendering - medium grit (1.5 mm)

Characteristics

- Very pleasant application.
- Covers substrate's irregularities.
- Weatherproof, shock-resistant and wear-resistant.
- Alkali-resistant.
- Water-repellent.
- Flexible film with high filling power.
- AFNOR NFT 30-700 classification - Family II - Class 2b.

Packaging options

20 kg

Application conditions

Ambient temperature between 10°C and 25°C with a substrate humidity of maximum 10%.

Application instructions

- The product is to be applied on a sound, clean and dry substrate.
- Glossy substrates are to be sanded before starting with application.
- Chalky or very absorbent substrates are to be treated with a consolidating primer beforehand.
- Dirty or infected (fungi and moulds) substrates are to be cleaned and degreased as well as undergo appropriate treatment.

Storing & disposal

Store the product in its original unopened packaging in a cool place, protected from frost and direct sunlight. Dispose of empty containers at an appropriate waste collection facility. Dispose of product residues in accordance with applicable local and national regulations.

Safety

Keep out of reach of children. Do not get in eyes, on skin or on clothing. Call a doctor if you feel unwell. If medical advice is needed, have product container or label at hand. Dispose of contents and container in accordance with local, regional, national or international regulations. Contains biocidal products (preservatives). Contains: 1,2-benzisothiazol-3(2H)-one + CMIT/MIT (3:1). May produce an allergic reaction.